



4 mm 4 mm Halfmoon direct drive (series 9)

851/9 C J PH bits, halfmoon



Application: Phillips screws

Drive: Halfmoon, 4 mm

Design: Hard

		 mm	 mm	 mm	 mm	 mm
05134605001 ¹⁾	PH 000	44	1 ⁴⁷ / ₆₄ "	1,5	20	²⁵ / ₃₂ "
05134606001 ¹⁾	PH 000	64	2 ³³ / ₆₄ "	1,5	20	²⁵ / ₃₂ "
05135270001 ¹⁾	PH 00	44	1 ⁴⁷ / ₆₄ "	1,8	20	²⁵ / ₃₂ "
05135271001 ¹⁾	PH 00	64	2 ³³ / ₆₄ "	1,8	20	²⁵ / ₃₂ "
05135272001 ²⁾	PH 0	44	1 ⁴⁷ / ₆₄ "	1,8	20	²⁵ / ₃₂ "
05135273001 ²⁾	PH 0	64	2 ³³ / ₆₄ "	1,8	20	²⁵ / ₃₂ "
05135274001 ²⁾	PH 0	44	1 ⁴⁷ / ₆₄ "	2,0	20	²⁵ / ₃₂ "
05135275001 ²⁾	PH 0	64	2 ³³ / ₆₄ "	2,2	20	²⁵ / ₃₂ "
05135278001 ²⁾	PH 0	44	1 ⁴⁷ / ₆₄ "	2,2	20	²⁵ / ₃₂ "
05135276001 ¹⁾	PH 1	44	1 ⁴⁷ / ₆₄ "	3,0	20	²⁵ / ₃₂ "
05135277001 ¹⁾	PH 1	64	2 ³³ / ₆₄ "	3,0	20	²⁵ / ₃₂ "
05134607001	PH 2	44	1 ⁴⁷ / ₆₄ "	4,0	-	-
05134608001	PH 2	64	2 ³³ / ₆₄ "	4,0	-	-

¹⁾ Optimised for Asian PH screws

²⁾ Size 0 modified according to JCIS 0 (Japanese Camera Industrial Standard)



4 mm 4 mm HIOS direct drive (series 21)

851/21 J bits



Application: Phillips screws

Drive: HIOS 4 mm

Design: Hard

		 mm	 mm	 mm
05135280001 ¹⁾	PH 00	40	1 ⁹ / ₁₆ "	1,8
05135281001 ¹⁾	PH 00	60	2 ³ / ₈ "	1,8
05135284001 ²⁾	PH 0	40	1 ⁹ / ₁₆ "	1,8
05135285001 ²⁾	PH 0	60	2 ³ / ₈ "	1,8
05135286001 ²⁾	PH 0	40	1 ⁹ / ₁₆ "	2,0
05135287001 ²⁾	PH 0	60	2 ³ / ₈ "	2,0
05135288001 ²⁾	PH 0	40	1 ⁹ / ₁₆ "	2,5
05135289001 ²⁾	PH 0	60	2 ³ / ₈ "	2,5
05135290001	PH 1	40	1 ⁹ / ₁₆ "	3,0
05135291001	PH 1	60	2 ³ / ₈ "	3,0

¹⁾ Size 00 modified according to JCIS 00 (Japanese Camera Industrial Standard) modifiziert

²⁾ Size 0 modified according to JCIS 0 (Japanese Camera Industrial Standard)

